

# Poster: Investigating TensorFlow for Airport Facial Identification

## Extended Abstract

Nikolay Shopov, Mingyu Jeong, Evin Rude, Brennan Nesoralla, Scott Hutchison, Alexander Mentis, Suzanne J. Matthews

Department of Electrical Engineering & Computer Science  
West Point, NY

[nikolay.shopov,mingyu.jeong,evin.rude,brennan.nesoralla,scott.hutchison,alexander.mentis,suzanne.matthews]  
@usma.edu

### CCS CONCEPTS

• **Computing methodologies** → *Computer vision; Neural networks*; • **Security and privacy** → *Usability in security and privacy*;

### KEYWORDS

facial identification, TensorFlow, deep learning, airport security

Facial recognition is a rapidly developing application of machine learning. Face identification is specifically being adopted across security systems such as airports, perimeter security, and law-enforcement. In this poster, we describe a facial identification approach that can be deployed at airports. Our contributions include i.) facial identification software built on top of Google's TensorFlow [1] framework; ii.) a data collection scheme that can be implemented at airports nationally; and iii.) a user interface for collecting data.

**Our airport booth:** To simulate data collection as it would occur at an airport, we built a mock security booth and use it to record subjects' faces (see Figure 1). The booth consists of 10 gray panel boards organized in a 2×5 configuration, and a rail system on which a web camera is mounted. Three LED tube lights are positioned to provide three-point lighting in the booth. The lighting system provides uniform lighting across differing lighting environments. A web-based user interface enables security personnel to capture video of individuals in the booth. A fifteen second video consisting of a 180° scan of each person's face is recorded at a frame rate of 24 frames per second. The user interface automatically extracts individual frames from the video and stores them with a unique ID. We use our system to collect a dataset of 72 individuals, with approximately 400 images for each individual.

**Facial Identification Approach:** Collected data is split into three subsets. 85% of the data is designated for training, while separate subsets of 10% and 5% are reserved for testing and validation respectively. Our initial model implements a Softmax Regression algorithm [2] available in TensorFlow. The model minimizes its cross-entropy by using back propagation and gradient decent with a learning rate of 0.5. We use a preliminary dataset of 72 subjects with 340 images per person for training, 40 for testing and 20 for validation. We feed batches of 128 images at a time to the model

This paper is authored by an employee(s) of the United States Government and is in the public domain. Non-exclusive copying or redistribution is allowed, provided that the article citation is given and the authors and agency are clearly identified as its source.

HoTSoS '18, April 10–11, 2018, Raleigh, NC, USA  
ACM ISBN 978-1-4503-6455-3/18/04.  
<https://doi.org/10.1145/3190619.3191692>




Figure 1: Data collection process

for training and train for 3,000 total iterations. We augment our approach by adding one layer of a neural network. Experimentation on an NVIDIA Tesla K40P yields accuracies of 90%. We plan to augment our approach further by adding layers of a Deep Convolutional Neural Network [3].

### ACKNOWLEDGMENTS

Funding for this project is provided for by the DOD High Performance Computing Modernization Program (HPCMP). We are grateful to HPCMP and the U.S. Army Engineer Research & Development Center (ERDC) for a grant of time on their supercomputer Topaz. The opinions in this work are solely of the authors and do not necessarily reflect those of the U.S. Military Academy, the U.S. Army, or the Department of Defense.

### REFERENCES

- [1] Martin Abadi, Paul Barham, Jianmin Chen, Zhifeng Chen, Andy Davis, Jeffrey Dean, Matthieu Devin, Sanjay Ghemawat, Geoffrey Irving, Michael Isard, et al. 2016. TensorFlow: A System for Large-Scale Machine Learning. In *OSDI*, Vol. 16. 265–283.
- [2] Christopher Bishop. 2006. *Pattern Recognition and Machine Learning* (1 ed.). Springer-Verlag New York.
- [3] Rama Chellappa, Jun-Cheng Chen, Rajeev Ranjan, Swami Sankaranarayanan, Amit Kumar, Vishal M Patel, and Carlos D Castillo. 2016. Towards the design of an end-to-end automated system for image and video-based recognition. In *Information Theory and Applications Workshop (ITA)*, 2016. IEEE, 1–7.